

**CEILING BRIDGE AND CEILING BACKBOX
MODEL S-550, S-551**

FEATURES:

FIRE RETARDANT DAMPING MATERIAL

FOUR COMBINATION 1/2" - 3/4" KNOCKOUTS

COMPATIBLE WITH 2' X 2', 2' X 4' CEILING GRIDS

LIGHTWEIGHT METAL CONSTRUCTION

COMPATIBLE WITH ROUND OR SQUARE BAFFLES



DESCRIPTION:

STEEL BRIDGE: Provides a solid mounting structure for ceiling speakers. The steel bridge prevents ceiling tile sag and is galvanized to inhibit rusting. This bridge may be used with all Clarity flush mount ceiling speakers.

BACKBOX: Prevent debris and insulation from coming into contact with the speaker. The sturdy metal construction of this backbox allows it to be used in plenum return ceilings. In open ceiling structures, the backbox may be used as an enclosure for a speaker by attaching the backbox directly to the beam and mounting a speaker to the backbox with the hardware provided.

SPECIFICATIONS:

DIMENSIONS AND WEIGHT

S-550

23.75" (60.3 cm) L x 14.5" (36.8 cm) W x 1.5" (3.8 cm)

Weight: 2 lbs (.9 kg)

S-551

12.3" (31.2 cm) D x 4" (10.2 cm) H

Weight: 2 lb (.9 kg)

MOUNTING

Extruded holes are provided for four #8 - 32 screws allowing for round or square baffles to be mounted. Both circular and square bolt patterns are existing. Suspension points are included for ceiling to speaker security.

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS MODEL S-550 CEILING BRIDGE AND MODEL S-551 CEILING BACKBOX

S-550

The Ceiling Speaker Bridge, Model S-550 shall be lightweight metal construction. It shall have four (4) extruded holes for #8 - 32 screws in two patterns. It shall have 1 1/4" diameter bolt circle and shall have a 10" x 10" square. It shall have 8 1/4" spaced slot for torsion springs. It shall be compatible with 2' x 2' and 2' x 4' drop ceiling tiles and the S-551 backbox. Dimensions shall be 23.75" (60.3 cm) L x 14.5" (36.8 cm) W x 1.5" (3.8 cm). The approximate weight shall be 2 lbs (.91 kg).

S-551

The Ceiling Backbox, Model S-551 shall be lined with an anti-resonant fire retardant material. It shall have four 1/2" and 3/4" knockouts at 90°. It shall be made of 22 gauge coated steel. Perforated steel straps shall be provided for hanging support wires. It shall be compatible with the S-550 bridge. Dimensions shall be 12.3" (31.2 cm) D x 4" (10.2 cm) H. The approximate weight shall be 2 lbs (.91 kg).

Limited Warranty

Clarity warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Clarity indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened. (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Clarity are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor).

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Clarity be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.